

PROJECTORS &  
DOCUMENT CAMERAS  
2021 LINE GUIDE



Projected images simulated










	Budget-friendly Classroom Projectors					Basic Projectors for Small & Medium Rooms
<b>Note:</b> Highlighted boxes indicate step-ups between models within a series.						
Epson® Model	<b>PowerLite® W70</b>	<b>PowerLite W75</b>	<b>PowerLite E20</b>	<b>PowerLite X49</b>	<b>PowerLite W49</b>	<b>PowerLite 1288</b>
Product Code	<b>V11HA20020</b>	<b>V11HA20120</b>	<b>V11H981020</b>	<b>V11H982020</b>	<b>V11H983020</b>	<b>V11H978120</b>
Replacement Lamp Code	<b>Laser</b>	<b>Laser</b>	<b>V13H010L97</b>	<b>V13H010L97</b>	<b>V13H010L97</b>	<b>V13H010L97</b>
Previous Epson Model			PowerLite S39	PowerLite X39	PowerLite W39	PowerLite 1286
Road Service Limited Warranty	2-year	2-year	2-year	2-year	2-year	2-year
<b>Basics</b>						
Color Brightness (Color Lumens)*	2,000	2,000	3,400	3,600	3,800	4,000
White Brightness (White Lumens)*	2,000	2,000	3,400	3,600	3,800	4,000
Native Resolution**	WXGA	WXGA	XGA	XGA	WXGA	1080p
Weight	6.1 lb	6.1 lb	5.9 lb	5.9 lb	5.9 lb	6.8 lb
Dimensions (Inches)†	8.3 x 9.1 x 3.6	8.3 x 9.1 x 3.6	11.8 x 9.8 x 3.6	11.8 x 9.8 x 3.6	11.8 x 9.8 x 3.6	12.1 x 11.5 x 4.1
Contrast Ratio (up to)	2,500,000:1	2,500,000:1	15,000:1	16,000:1	16,000:1	16,000:1
Throw Ratio	1.04 Wide, 1.40 Tele	1.04 Wide, 1.40 Tele	1.44 Wide, 1.95 Tele	1.48 Wide, 1.77 Tele	1.30 Wide, 1.56 Tele	1.32 Wide, 2.14 Tele
Zoom Lens (Ratio)	1.0 - 1.35 (Digital Zoom)	1.0 - 1.35 (Digital Zoom)	1.35x Digital	1.2x Optical	1.2x Optical	1.6x Optical
Light Source	Laser	Laser	Lamp	Lamp	Lamp	Lamp
Light Source Life Cycle up to (Normal/Medium/ECO [Hours])††	12,000	12,000	6,000/-/12,000	6,000/-/12,000	8,000/10,000/17,000	5,500/-/12,000
Power Consumption	178 W	178 W	345 W	345 W	345 W	345 W
<b>Value-added Features</b>						
Built-in Speaker	5 W	5 W	5 W	5 W	5 W	16 W
Closed Captioning	–	–	YES	YES	YES	YES
A/V Mute	YES	YES	Slide Door	Slide Door	Slide Door	Slide Door
Split Screen	–	–	YES	YES	YES	YES
Edge Blending	–	–	–	–	–	–
Curved Wall, Corner Wall	–	–	–	–	–	–
Scheduling Function	–	–	–	–	–	–
<b>Easy Connectivity and Setup</b>						
Epson iProjection™ Suite (Moderator, Multi-PC, Device Management)***	–	–	–	YES	YES	YES
Epson Creative Content Projection App for Signage****	–	–	–	–	–	–
Epson Projector Content Manager Software****	–	–	–	–	–	–
Miracast®	–	–	–	–	–	YES
USB Plug 'n Play Image/Video	–	–	–	YES	YES	YES
PC-free Presentations via USB Type-A	–	–	–	Images	Images	Photo, Motion JPEG
Quick Corner® Adjustments	YES	YES	YES	YES	YES	YES
Screen Fit	–	–	–	–	–	–
Keystone (Horizontal/Vertical)	YES	YES	Manual/Manual	Manual/Auto	Manual/Auto	Manual/Auto
Easy-slide Horizontal Keystone Adjustment	–	–	YES	YES	YES	YES
Lens Shift (Vertical and Horizontal)	–	–	–	–	–	–
<b>LAN Networking and Control</b>						
Wired	–	–	–	RJ-45 (Content over IP)	RJ-45 (Content over IP)	–
Wireless	–	–	–	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Included (802.11 b/g/n) QR Code Quick Connect
Compatible Control Systems	–	–	–	Crestron®, AMX®, Extron®, Control4®	Crestron, AMX, Extron, Control4	–
<b>Connections</b>						
HDMI®	HDMI x 1	HDMI x 1	HDMI x 1	HDMI x 1	HDMI x 2	HDMI x 2
Analog Connections	–	–	VGA x 2, Composite x 1	VGA x 2, Composite x 1	VGA x 2, Composite x 1	VGA x 1, Composite x 1
Audio In	–	–	RCA (L & R) x 1 Mini Stereo x 2	RCA (L & R) x 1 Mini Stereo x 2	RCA (L & R) x 1 Mini Stereo x 2	RCA x 1
Variable Audio Out	Mini Stereo x 1 Bluetooth® 3.0 Class 2 (2.4GHz)	Mini Stereo x 1 Bluetooth 3.0 Class 2 (2.4GHz)	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	–
USB 2.0 Connectors	–	–	Type-B x 1	Type-A, Type-B	Type-A, Type-B	–
DisplayPort/DVI-D	–	–	–	–	–	–
HDBaseT™	–	–	–	–	–	–
SDI	–	–	–	–	–	–
Monitor Out	–	–	D-sub 15-pin x 1	D-sub 15-pin x 1	D-sub 15-pin x 1	–
Serial Control	–	–	RS-232c x 1	RS-232c x 1	RS-232c x 1	–
<b>Recommended Accessory 1</b>	Ceiling Mount White (ELPMB60W)	Ceiling Mount Black (ELPMB60B)	Soft Carrying Case	Wireless LAN Module	Wireless LAN Module	ES3000 Screen
<b>Recommended Accessory 1 SKU</b>	V12963210	V12H963110	V12H00K70	V12H005A02	V12H005A02	V12H002S3Y
<b>Recommended Accessory 2</b>	–	–	DC-13 Document Camera	DC-13 Document Camera	DC-13 Document Camera	Soft Carrying Case
<b>Recommended Accessory 2 SKU</b>	–	–	V12H757020	V12H757020	V12H757020	V12H001K70

\*Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. \*\*WXGA (1920 x 1200), WXGA (1280 x 800), XGA (1024 x 768), SVGA (800 x 600). \*\*\*For wireless functionality, including via the Epson iProjection App, the projector must be configured on a network, either through the Ethernet port on the projector (check model specifications for availability) or via a wireless connection. Check your owner's manual to determine if a wireless LAN module must be purchased separately to enable a wireless connection. Not all Epson projectors are able to be networked. The Epson iProjection App does not support all files and formats. See www.epson.com for details. \*\*\*\*Internet connection required for download. Data usage fees may apply.

Advanced Networking Classroom Projectors Standard-throw					Advanced Networking Classroom Projectors Short-throw		
							
<b>PowerLite 118</b>	<b>PowerLite 119W</b>	<b>PowerLite U50</b>	<b>PowerLite 982W</b>	<b>PowerLite 992F</b>	<b>PowerLite 530</b>	<b>PowerLite 535W</b>	<b>PowerLite L200SX</b>
V11HA03020	V11H985020	V11H952020	V11H987020	V11H988020	V11H673020	V11H671020	V11H994020
V13H010L97	V13H010L97	V13H010L97	V13H010L97	V13H010L97	V13H010L87	V13H010L87	N/A
PowerLite 108	PowerLite 109W	PowerLite 975W	PowerLite 980W	PowerLite 990U	PowerLite 430	PowerLite 435W	–
2-year	2-year	2-year	2-year	2-year	2-year	2-year	3-year
3,800	4,000	3,700	4,200	4,000	3,200	3,400	3,600
3,800	4,000	3,700	4,200	4,000	3,200	3,400	3,600
XGA	WXGA	WUXGA	WXGA	1080p	XGA	WXGA	XGA
6.2 lb	6.2 lb	6.8 lb	6.8 lb	6.8 lb	8.2 lb	8.2 lb	9.9 lb.
11.8 x 10.2 x 3.6	11.8 x 10.2 x 3.6	14.3 x 9.8 x 3.7	12.2 x 11.5 x 4.1	12.2 x 11.5 x 4.1	13.5 x 12.5 x 5.2	13.5 x 12.5 x 5.2	12.8 x 3.6 x 13.3
16,000:1	16,000:1	16,000:1	16,000:1	16,000:1	16,000:1	16,000:1	2,500,00:1
1.48 Wide, 1.77 Tele	1.38 Wide, 1.56 Tele	1.38 Wide, 1.68 Tele	1.38 Wide, 2.24 Tele	1.32 Wide, 2.14 Tele	0.55 Wide, 0.74 Tele	0.48 Wide, 0.65 Tele	0.55 Wide, 0.74 Tele
1.2x Optical	1.2x Optical	1.2x Optical	1.6x Optical	1.6x Optical	1.35x Digital	1.35x Digital	1.35x Digital
Lamp	Lamp	Lamp	Lamp	Lamp	Lamp	Lamp	Laser
8,000/10,000/17,000	8,000/10,000/17,000	10,000/-/17,000	6,500/10,000/17,000	6,500/10,000/17,000	5,000-/10,000	5,000-/10,000	20,000-/30,000
345 W	345 W	298 W	345 W	345 W	315 W	315 W	265 W
16 W	16 W	5 W	16 W	16 W	16 W	16 W	16 W
YES	YES	YES	YES	YES	YES	YES	YES
Slide Door	Slide Door	Slide Door	Slide Door	Slide Door	Digital	Digital	Digital
YES	YES	YES	YES	YES	–	–	YES
–	–	–	–	–	–	YES	–
–	–	–	–	–	–	–	–
–	–	YES	–	–	–	–	–
YES	YES	YES	YES	YES	YES	YES	YES
–	–	–	–	–	–	–	–
–	–	–	–	–	–	–	–
–	–	–	–	YES	–	–	YES
YES	YES	YES	YES	YES	YES	YES	YES
Images, PDFs	Images, PDFs	Images, PDFs	Images, PDFs	Images, PDFs	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES	YES
–	–	–	–	–	–	–	–
Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Manual	Manual/Manual	Manual/Manual
YES	YES	–	YES	YES	–	–	–
–	–	–	–	–	–	–	–
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Included (802.11 b/g/n)	Optional (802.11 b/g/n)	Included (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Included 802.11a/b/g/n/ac; 5GHz
Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron	Crestron, AMX, Extron	Crestron, AMX, Extron, Art-Net, PJLink
HDMI x 2	HDMI x 2	HDMI x 2	HDMI x 2	HDMI x 2	HDMI x 1	HDMI x 1	HDMI x 2
VGA x 2, Composite x 1	VGA x 2, Composite x 1	VGA x 2	VGA x 2, Composite x 1	VGA x 2, Composite x 1	VGA x 2, S-video, Composite Video	VGA x 2, S-video, Composite Video	VGA x 2, Composite Video
RCA (L & R) x 1 Mini Stereo x 2	RCA (L & R) x 1 Mini Stereo x 2	Mini Stereo x 2	RCA (L & R) x 1 Mini Stereo x 2	RCA (L & R) x 1 Mini Stereo x 2	RCA (L & R) x 1 Mini Stereo x 2, Mic-in	RCA (L & R) x 1 Mini Stereo x 2, Mic-in	RCA (L & R) x 1 Mini Stereo x 2, Mic in
Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1
Type-A, Type-B	Type-A, Type-B	Type-A, Type-B	Type-A, Type-B	Type-A, Type-B	Type-A, Type-B	Type-A, Type-B	Type-A, Type-B
–	–	–	–	–	–	–	–
–	–	–	–	–	–	–	–
–	–	–	–	–	–	–	–
D-sub 15-pin x 1	D-sub 15-pin x 1	Mini D-sub 15-pin x 1	D-sub 15-pin x 1	D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1
RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1
Wireless LAN Module	Wireless LAN Module	ELPMB60 Ceiling Mount	Wireless LAN Module	Universal Mount (ELPMBPJG)	Short-throw Wall Mount (ELPMB45)	Short-throw Wall Mount (ELPMB45)	Short-throw Wall Mount (ELPMB64)
V12H005A02	V12H005A02	V12H963010	V12H005A02	V12H808001	V12H706020	V12H706020	V12HA39010
DC-21 Document Camera	DC-21 Document Camera	DC-21 Document Camera	DC-21 Document Camera	DC-21 Document Camera	PowerLite Pilot™ 3 Connection and Control Box (ELPCB03)	PowerLite Pilot 3 Connection and Control Box (ELPCB03)	PowerLite Pilot 3 Connection and Control Box (ELPCBA39010)
V12H758020	V12H758020	V12H758020	V12H758020	V12H758020	V12H927020	V12H927020	V12HA39010


†Dimensions including feet and standard lens.

††Maximum lamp life will vary depending upon mode selected, environmental conditions, and usage. Brightness decreases over time. The lamp comes with a 90-day limited warranty.

	Advanced Networking Classroom Projectors Ultra Short-throw			Short- and Ultra Short-throw Projectors for SMART		
						
<b>PowerLite L200SW</b>	<b>PowerLite 680</b>	<b>PowerLite 685W</b>	<b>PowerLite 720</b>	<b>PowerLite 725W</b>	<b>PowerLite 750F</b>	<b>PowerLite 755F</b>
V11H993020	V11H746520	V11H744520	V11HA01520	V11H999520	V11HA08520	V11HA08620
N/A	V13H010L91	V13H010L91	Laser	Laser	Laser	Laser
–	PowerLite 580	PowerLite 585W	–	–	–	–
3-year	2-year	2-year	3-year <sup>A</sup>	3-year <sup>A</sup>	3-year <sup>A</sup>	3-year <sup>A</sup>
3,800	3,500	3,500	3,800	4,000	3,600	3,600
3,800	3,500	3,500	3,800	4,000	3,600	3,600
WXGA	XGA	WXGA	XGA	WXGA	1080p	1080p
9.9 lb.	12.6 lb	12.6 lb	12.5 lb	12.5 lb	12.5 lb	12.5 lb
12.8 x 3.6 x 13.3	14.5 x 15.8 x 7.4	14.5 x 15.8 x 7.4	14.1 x 15.6 x 5.25	14.1 x 15.6 x 5.25	14.1 x 15.6 x 5.25	14.1 x 15.6 x 5.25
2,500,00:1	14,000:1	14,000:1	2,500,000:1	2,500,000:1	Dynamic 2,500,000:1 Native 1,400:1	Dynamic 2,500,000:1 Native 1,400:1
0.48 Wide, 0.65 Tele	0.32 Wide, 0.43 Tele	0.28 Wide, 0.37 Tele	0.32 Wide, 0.43 Tele	0.28 Wide, 0.37 Tele	0.26 Wide, 0.36 Tele	0.26 Wide, 0.36 Tele
1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital	1.35x Digital
Laser	Lamp	Lamp	Laser	Laser	Laser	Laser
20,000/-/30,000	5,000/-/10,000	5,000/-/10,000	20,000/-/30,000	20,000/-/30,000	20,000/-/30,000	20,000/-/30,000
265 W	373 W	373 W	267 W	267 W	267 W	267 W
16 W	16 W	16 W	16 W	16 W	16 W	16 W
YES	YES	YES	YES	YES	YES	YES
Digital	Digital	Digital	Digital	Digital	Digital	Digital
YES	YES	YES	YES	YES	YES	YES
–	YES	–	–	–	YES	YES
–	–	–	–	–	–	–
YES	YES	–	–	–	YES	YES
YES	YES	YES	YES	YES	YES	YES
–	–	–	–	–	–	–
–	–	–	–	–	–	–
–	–	–	–	–	–	–
Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual
–	–	–	–	–	–	–
–	–	–	–	–	–	–
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Included 802.11a/b/g/n/ac; 5GHz	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Included (802.11a/b/g/n/ac); 5GHz	Included (802.11a/b/g/n/ac); 5GHz	Included 802.11b/g/n (2.4GHz) 802.11a/n/ac (5GHz)	Included 802.11b/g/n (2.4GHz) 802.11a/n/ac (5GHz)
Crestron, AMX, Extron, Art-Net, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, PJLink, Art-Net, AMX, Control4	Crestron, AMX, Extron, PJLink, Art-Net, AMX, Control4
HDMI x 2	HDMI x 3 (Includes MHL® x 1)	HDMI x 3 (Includes MHL x 1)	HDMI x 3	HDMI x 3	HDMI x 3	HDMI x 3
VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video
RCA (L & R) x 1 Mini Stereo x 2, Mic in	Mini Stereo x 3	Mini Stereo x 3	Mini Stereo x 3	Mini Stereo x 3 Mic-in	Mini Stereo x 3	Mini Stereo x 3
Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1
Type-A, Type-B	Type-A, Type-B	Type-A, Type-B	Type-B x 1, Type-A x 2	Type-B x 1, Type-A x 2	Type-B x 1, Type-A x 2	Type-B x 1, Type-A x 2
–	–	–	–	–	–	–
–	–	–	–	–	–	–
–	–	–	–	–	–	–
Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1
RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1
Short-throw Wall Mount (ELPMB64)	Ultra Short-throw Wall Mount (ELPMB46)	Ultra Short-throw Wall Mount (ELPMB46)	Ultra Short-throw Wall Mount (ELPMB62)	Ultra Short-throw Wall Mount (ELPMB62)	Ultra Short-throw Wall Mount (ELPMB62)	Ultra Short-throw Wall Mount (ELPMB62)
V12HA39010	V12H777020	V12H777020	V12HA06A05	V12HA06A05	V12HA06A05	V12HA06A05
PowerLite Pilot 3 Connection and Control Box (ELPCBA39010)	PowerLite Pilot 3 Connection and Control Box (ELPCB03)	PowerLite Pilot 3 Connection and Control Box (ELPCB03)	DC-21 Document Camera	DC-21 Document Camera	DC-21 Document Camera	PowerLite Pilot 3 Connection and Control Box (ELPCB03)
V12HA39010	V12H927020	V12H927020	V12H758020	V12H758020	V12H758020	V12H927020

		Ultra Mobile Projectors – 1700 Series Extra Thin and Light			
					
<b>PowerLite 800F</b>	<b>PowerLite 805F</b>	<b>PowerLite 1780W</b>	<b>PowerLite 1781W</b>	<b>PowerLite 1785W</b>	<b>PowerLite 1795F</b>
V11H923520	V11H923620	V11H795020	V11H794120	V11H793020	V11H796020
Laser	Laser	V13H010L94	V13H010L94	V13H010L94	V13H010L94
PowerLite 700U	PowerLite 700U	PowerLite 1761W	PowerLite 1771W	PowerLite 1776W	–
3-year <sup>‡</sup>	3-year <sup>‡</sup>	2-year	2-year	2-year	2-year
5,000	5,000	3,000	3,200	3,200	3,200
5,000	5,000	3,000	3,200	3,200	3,200
1080p	1080p	WXGA	WXGA	WXGA	1080p
21.4 lb	21.4 lb	4.0 lb	4.0 lb	4.0 lb	4.0 lb
18.1 x 17.7 x 9.0	18.1 x 17.7 x 9.0	11.5 x 8.4 x 2.1	11.5 x 8.4 x 2.1	11.5 x 8.4 x 2.1	11.5 x 8.4 x 2.1
Dynamic 2,500,000:1 Native 1,440:1	Dynamic 2,500,000:1 Native 1,440:1	10,000:1	10,000:1	10,000:1	10,000:1
0.27 Wide, 0.37 Tele	0.27 Wide, 0.37 Tele	1.04 Wide, 1.26 Tele	1.04 Wide, 1.26 Tele	1.04 Wide, 1.26 Tele	1.02 Wide, 1.23 Tele
1.35x Digital	1.35x Digital	1.2x Optical	1.2x Optical	1.2x Optical	1.2x Optical
Laser	Laser	Lamp	Lamp	Lamp	Lamp
20,000/-/30,000	20,000/-/30,000	4,000/-/7,000	4,000/-/7,000	4,000/-/7,000	4,000/-/7,000
381 W	381 W	290 W	290 W	309 W	309 W
2 x 8 W	2 x 8 W	1 W	1 W	1 W	1 W
YES	YES	YES	YES	YES	YES
Digital	Digital	Slide Door	Slide Door	Slide Door	Slide Door
YES	YES	YES	YES	YES	YES
YES	YES	–	–	–	–
–	–	–	–	–	–
YES	YES	–	–	–	–
YES	YES	YES	YES	YES	YES
YES	YES	–	–	YES	YES
YES	YES	YES	YES	YES	YES
YES	YES	Video, Images	Video, Images	Video, Images, PDF	Video, Images, PDF
YES	YES	YES	YES	YES	YES
–	–	–	–	YES	YES
Manual/Manual	Manual/Manual	Manual/Auto	Manual/Auto	Auto/Auto	Auto/Auto
–	–	–	–	–	–
–	–	–	–	–	–
RJ-45 (Content over IP)	RJ-45 (Content over IP)	–	–	–	–
Optional 802.11b/g/n (2.4GHz) 802.11a/n/ac (5GHz)	Optional 802.11b/g/n (2.4GHz) 802.11a/n/ac (5GHz)	Included (802.11 b/g/n)	Included (802.11 b/g/n)	Included (802.11 b/g/n)	Included (802.11 b/g/n)
Crestron, AMX, Extron, PJLink, Art-Net, AMX, Control4	Crestron, AMX, Extron, PJLink, Art-Net, AMX, Control4	–	–	–	–
HDMI x 3	HDMI x 3	HDMI x 1	HDMI x 1	HDMI x 1	HDMI x 1
VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 1, Composite Video	VGA x 1, Composite Video	VGA x 1, Composite Video	VGA x 1, Composite Video
Mini Stereo x 3	Mini Stereo x 3	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1
Mini Stereo x 1	Mini Stereo x 1	–	–	–	–
Type-B x 1, Type-A x 2	Type-B x 1, Type-A x 2	Type-A, Type-B	Type-A, Type-B	Type-A, Type-B	Type-A, Type-B
–	–	–	–	–	–
YES	YES	–	–	–	–
–	–	–	–	–	–
Mini D-sub 15-pin x 1, HDMI out	Mini D-sub 15-pin x 1, HDMI out	–	–	–	–
RS-232c x 1	RS-232c x 1	–	–	–	–
Ultra Short-throw Wall Mount (ELPMB62)	HDBaseT Transmitter	ES3000 Screen	ES3000 Screen	ES3000 Screen	ES3000 Screen
V12HA06A05	V12H547020	V12H002S3Y	V12H002S3Y	V12H002S3Y	V12H002S3Y
Wireless Lan Module	Wireless Lan Module	DC-21 Document Camera	DC-21 Document Camera	DC-21 Document Camera	DC-21 Document Camera
V12H005A02	V12H005A02	V12H758020	V12H758020	V12H758020	V12H758020

‡ 20,000 hours is the estimated laser light source life when used in Normal Mode. Actual hours may vary depending on mode and usage environment. The projector has a standard limited warranty of 3 years.  
<sup>Δ</sup> 5-year with product registration.

	Meeting Room and Large Room Projectors – 2000 Series				PowerLite Long-throw Laser Projectors		
<b>Note:</b> Highlighted boxes indicate step-ups between models within a series.							
Epson Model	<b>PowerLite 2065</b>	<b>PowerLite 2247U</b>	<b>PowerLite 2250U</b>	<b>PowerLite 2255U</b>	<b>PowerLite L200X</b>	<b>PowerLite L200W</b>	<b>PowerLite L250F</b>
Product Code	<b>V11H820020</b>	<b>V11H881020</b>	<b>V11H871020</b>	<b>V11H815020</b>	<b>V11H992020</b>	<b>V11H991020</b>	<b>V11HA17020</b>
Replacement Lamp Code	<b>V13H010L95</b>	<b>V13H010L96</b>	<b>V13H010L95</b>	<b>V13H010L95</b>	Laser	Laser	Laser
Previous Epson Model	PowerLite 1960/1965	PowerLite 2245U	PowerLite 1980WU	PowerLite 1985WU	–	–	–
Road Service Limited Warranty	2-year	2-year	2-year	2-year	3-year	3-year	3-year
<b>Basics</b>							
Color Brightness (Color Lumens)*	5,500	4,200	<b>5,000</b>	5,000	4,200	4,200	4,500
White Brightness (White Lumens)*	5,500	4,200	<b>5,000</b>	5,000	4,200	4,200	4,500
Native Resolution**	XGA	<b>WUXGA</b>	WUXGA	WUXGA	XGA	WXGA	1080p
Weight	9.7 lb	7.1 lb	10.2 lb	10.1 lb	9.1 lb	9.1 lb	9.1 lb
Dimensions (Inches)†	14.9 x 11.5 x 4.6	14.9 x 11.5 x 5.0	14.9 x 11.5 x 5.0	14.9 x 11.5 x 5.0	12.8 x 11.8 x 4.1	12.8 x 11.8 x 4.1	12.8 x 11.8 x 4.1
Contrast Ratio (up to)	15,000:1	15,000:1	15,000:1	15,000:1	2,500,000:1	2,500,000:1	2,500,000:1
Throw Ratio	1.38 Wide, 2.24 Tele	1.39 Wide, 2.23 Tele	1.38 Wide, 2.28 Tele	1.57 Wide, 2.58 Tele	1.32 - 2.15	1.38 - 2.24	1.33 - 2.16
Zoom Lens (Ratio)	1.0 – 1.6x Optical	1.0 – 1.6x Optical	1.0 – 1.6x Optical	1.0 – 1.6x Optical	1.0 – 1.6x Optical	1.0 – 1.6x Optical	1.0 – 1.6x Optical
Light Source	Lamp	Lamp	Lamp	Lamp	Laser	Laser	Laser
Light Source Life Cycle up to (Normal/ECO [Hours])††	5,000/10,000	5,500/12,000	5,000/10,000	5,000/10,000	20,000 hours‡	20,000 hours‡	20,000 hours‡
Power Consumption	333 W	350 W	429 W	429 W	265 W	265 W	265 W
<b>Value-added Features</b>							
Built-in Speaker	16 W	16 W	16 W	16 W	16 W	16 W	16 W
Closed Captioning	YES	YES	YES	YES	YES	YES	YES
A/V Mute	YES	YES	YES	YES	YES	YES	YES
Split Screen	YES	YES	YES	YES	YES	YES	YES
Edge Blending	–	–	–	–	–	–	<b>YES</b>
Curved Surface and Corner Wall	–	–	–	–	–	–	–
Scheduling Function	YES	YES	YES	YES	YES	YES	YES
<b>Easy Connectivity and Setup</b>							
Epson iProjection Suite (Moderator, Multi-PC, Device Management)***	YES	YES	YES	YES	YES	YES	YES
Epson Creative Content Projection App for Signage****	–	–	–	–	–	–	<b>YES</b>
Epson Projector Content Manager Software****	–	–	–	–	–	–	<b>YES</b>
Miracast	–	YES	–	<b>YES</b>	YES	YES	YES
USB Plug 'n Play Image/Video	YES	YES	YES	YES	YES	YES	YES
PC-free Presentations via USB Type-A	YES	YES	YES	YES	YES	YES	YES
Quick Corner Adjustments	YES	YES	YES	YES	YES	YES	YES
Screen Fit	–	–	–	–	–	–	–
Keystone (Horizontal/Vertical)	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto
Easy-slide Horizontal Keystone Adjustment	–	YES	–	–	YES	YES	YES
Lens Shift (Vertical and Horizontal)	–	–	–	–	–	–	–
<b>LAN Networking and Control</b>							
Wired	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Wireless	Included (802.11 b/g/n) QR Code Quick Connect	Included (802.11 b/g/n) QR Code Quick Connect	Optional (802.11 b/g/n)	<b>Included (802.11 b/g/n) Connect QR Code</b>	Included (802.11 b/g/n/a/ac) 2.4 GHz and 5GHz	Included (802.11 b/g/n/a/ac) 2.4 GHz and 5GHz	Included 802.11b/g/n (2.4GHz) 802.11a/n/ac (5GHz)
Compatible Control Systems	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, P.J.Link, Art-Net, AMX, Control4
<b>Connections</b>							
HDMI	HDMI x 2 (Includes MHL x 1)	HDMI x 2 (Includes MHL x 1)	HDMI x 2 (Includes MHL x 1)	HDMI x 2 (Includes MHL x 1)	HDMI x 2	HDMI x 2	HDMI x 2
Analog Connections	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video
Audio In	RCA (L & R) x 1 Mini Stereo x 2	RCA (L & R) x 1 Mini Stereo x 2	RCA (L & R) x 1 Mini Stereo x 2	RCA (L & R) x 1 Mini Stereo x 2	RCA (L & R) x 1 Mini Stereo x 2	RCA (L & R) x 1 Mini Stereo x 2	RCA (L & R) x 1 Mini Stereo x 2
Variable Audio Out	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1
USB 2.0 Connectors	Type-A, Type-B	Type-A, Type-B	Type-A, Type-B	Type-A, Type-B	Type-A, Type-B	Type-A, Type-B	Type-A, Type-B
DisplayPort/DVI-D	–	–	–	–	–	–	–
HDBaseT	–	–	–	–	–	–	–
SDI	–	–	–	–	–	–	–
Monitor Out	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1
Serial Control	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1
<b>Recommended Accessory 1</b>							
Recommended Accessory 1 SKU	Universal Projector Mount (ELPMBPJG)	Universal Projector Mount (ELPMBPJG)	Universal Projector Mount (ELPMBPJG)	Universal Projector Mount (ELPMBPJG)	Ceiling Mount (ELPMB60W)	Ceiling Mount (ELPMB60W)	Ceiling Mount (ELPMB60W)
Recommended Accessory 2	Replacement Air Filter (ELPAF41)	Replacement Air Filter (ELPAF55)	Wireless LAN Module	Replacement Air Filter (ELPAF41)	Replacement Air Filter (ELPAF60)	Replacement Air Filter (ELPAF60)	Replacement Air Filter (ELPAF60)
Recommended Accessory 2 SKU	V13H134A41	V13H134A55	V12H731P02	V13H134A41	V13H134A60	V13H134A60	V13H134A60

\*Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IESNA 15.4; white light output measured in accordance with ISO 21118.  
 \*\*WUXGA (1920 x 1200), WXGA (1280 x 800), XGA (1024 x 768), SVGA (800 x 600). \*\*\*For wireless functionality, including via the Epson iProjection App, the projector must be configured on a network, either through the Ethernet port on the projector (check model specifications for availability) or via a wireless connection. Check your owner's manual to determine if a wireless LAN module must be purchased separately to enable a wireless connection. Not all Epson projectors are able to be networked. The Epson iProjection App does not support all files and formats. See www.epson.com for details. \*\*\*\*Internet connection required for download. Data usage fees may apply.

PowerLite L Series Laser Projectors for Meeting Rooms and Large Rooms							
							
<b>PowerLite L255F</b>	<b>PowerLite L400U</b>	<b>PowerLite L500W</b>	<b>PowerLite L510U</b>	<b>PowerLite L610</b>	<b>PowerLite L610W</b>	<b>PowerLite L610U</b>	<b>PowerLite L615U</b>
<b>V11HA17120</b>	<b>V11H907020</b>	<b>V11H908020</b>	<b>V11H903020</b>	<b>V11H905020</b>	<b>V11H904020</b>	<b>V11H901020</b>	<b>V11H901120</b>
<b>Laser</b>	<b>Laser</b>	<b>Laser</b>	<b>Laser</b>	<b>Laser</b>	<b>Laser</b>	<b>Laser</b>	<b>Laser</b>
–	–	–	–	–	–	–	–
3-year	3-year	3-year	3-year	3-year	3-year	3-year	3-year
4,500	4,500	5,000	5,000	6,000	6,000	6,000	6,000
4,500	4,500	5,000	5,000	6,000	6,000	6,000	6,000
1080p	WUXGA	WXGA	WUXGA	XGA	WXGA	WUXGA	WUXGA
9.1 lb	17.1 lb	16.3 lb	18.7 lb	18.7 lb	18.7 lb	18.7 lb	18.7 lb
12.8 x 11.8 x 4.1	17.4 x 12.0 x 5.4	17.4 x 12.0 x 5.4	17.4 x 12.0 x 5.4	17.4 x 12.0 x 5.4	17.4 x 12.0 x 5.4	17.4 x 12.0 x 5.4	17.4 x 12.0 x 5.4
2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1
1.33 - 2.16	1.35 - 2.20	1.38 - 2.24	1.35 - 2.20	1.52 - 2.47	1.35 - 2.20	1.35 - 2.20	1.35 - 2.20
1.0 - 1.6x Optical	1.0 - 1.6x Optical	1.0 - 1.6x Optical	1.0 - 1.6x Optical	1.0 - 1.6x Optical	1.0 - 1.6x Optical	1.0 - 1.6x Optical	1.0 - 1.6x Optical
Laser	Laser	Laser	Laser	Laser	Laser	Laser	Laser
20,000 hours <sup>†</sup>	20,000 hours <sup>†</sup>	20,000 hours <sup>†</sup>	20,000 hours <sup>†</sup>	20,000 hours <sup>†</sup>	20,000 hours <sup>†</sup>	20,000 hours <sup>†</sup>	20,000 hours <sup>†</sup>
265 W	324 W	337 W	337 W	370 W	370 W	370 W	370 W
16 W	10 W	10 W	10 W	10 W	10 W	10 W	10 W
YES	–	–	–	–	–	–	–
YES	YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES	YES
YES	–	–	–	–	–	–	–
–	–	–	–	–	–	–	–
YES	YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES	YES
–	–	–	–	–	–	–	–
Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto
YES	–	–	–	–	–	–	–
–	–	–	V ±50%, H ±20%	V ±50%, H ±30%	V ±50%, H ±20%	V ±50%, H ±20%	V ±50%, H ±20%
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Included (802.11b/g/n (2.4GHz) 802.11a/n/ac (5GHz))	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Included (802.11 b/g/n/a/ac), 2.4 GHz and 5GHz	Included (802.11 b/g/n/a/ac), 2.4 GHz and 5GHz
Crestron, AMX, Extron, PJLink, Art-Net, AMX, Control4	Crestron, AMX, PJLink, Control4	Crestron, AMX, PJLink, Control4	Crestron, AMX, PJLink, Control4	Crestron, AMX, PJLink, Control4	Crestron, AMX, PJLink, Control4	Crestron, AMX, PJLink, Control4	Crestron, AMX, PJLink, Control4
HDMI x 2	HDMI x 2 (Includes MHL x 1)	HDMI x 2	HDMI x 2	HDMI x 2	HDMI x 2	HDMI x 2	HDMI x 2
VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2	VGA x 2	VGA x 2	VGA x 2	VGA x 2	VGA x 2
RCA (L & R) x 1 Mini Stereo x 2	RCA (L & R) x 1 Mini Stereo x 2	Mini Stereo x 2	Mini Stereo x 2	Mini Stereo x 2	Mini Stereo x 2	Mini Stereo x 2	Mini Stereo x 2
Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1
Type-A, Type-B	Type-A, Type-B	Type-A, Type-B	Type-A, Type-B	Type-A, Type-B	Type-A, Type-B	Type-A, Type-B	Type-A, Type-B
–	–	–	–	–	–	–	–
–	–	–	HDBaseT x 1	–	HDBaseT x 1	HDBaseT x 1	HDBaseT x 1
–	–	–	–	–	–	–	–
Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1
RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1
Ceiling Mount (ELPMB60)	Universal Projector Mount (ELPMBPJG/ELPM3PRH)	Universal Projector Mount (ELPMBPJG/ELPM3PRH)	Universal Projector Mount (ELPMBPJG/ELPM3PRH)	Universal Projector Mount (ELPMBPJG/ELPM3PRH)	Universal Projector Mount (ELPMBPJG/ELPM3PRH)	Universal Projector Mount (ELPMBPJG/ELPM3PRH)	Universal Projector Mount (ELPMBPJG/ELPM3PRH)
V12H963110	V12H808001/V12H809001	V12H808001/V12H809001	V12H808001/V12H809001	V12H808001/V12H809001	V12H808001/V12H809001	V12H808001/V12H809001	V12H808001/V12H809001
Replacement Air Filter (ELPAF60)	Replacement Air Filter (ELPAF56)	Replacement Air Filter (ELPAF56)	HDBaseT Transmitter	Replacement Air Filter (ELPAF56)	HDBaseT Transmitter	HDBaseT Transmitter	HDBaseT Transmitter
V13H134A60	V13H134A56	V13H134A56	V12H547020	V13H134A56	V12H547020	V12H547020	V12H547020

<sup>†</sup>Dimensions including feet and standard lens.

<sup>††</sup>Maximum lamp life will vary depending upon mode selected, environmental conditions, and usage. Brightness decreases over time. The lamp comes with a 90-day limited warranty.

Large Meeting Room – 5000 Series Basic Installation Projectors	Large Venue Installation – Pro G Series Lamp-based Projectors with Optional Lenses							
								
<b>PowerLite 5535U</b>	<b>Pro G7805</b>	<b>Pro G7200W</b>	<b>Pro G7500U</b>	<b>Pro L1060WNL</b>	<b>Pro L1070WNL</b>	<b>Pro L1060UNL</b>	<b>Pro L1070UNL</b>	<b>Pro L1075UNL</b>
V11H824120	V11H753120	V11H751020	V11H750020	V11H958920	V11H957920	V11H941920	V11H940920	V11H940820
V13H010L95	V13H010L93	V13H010L93	V13H010L93	Laser	Laser	Laser	Laser	Laser
PowerLite 4855WU	–	–	–	Pro G7000W	Pro G7000W	Pro L1100U	Pro L1200U	Pro L1200U
2-year	3-year or 20,000 hours	3-year or 20,000 hours	3-year or 20,000 hours	3-year or 20,000 hours	3-year or 20,000 hours	3-year or 20,000 hours	3-year or 20,000 hours	3-year or 20,000 hours
5,500	8,000	7,500	6,500	6,000	7,000	6,000	7,000	7,000
5,500	8,000	7,500	6,500	6,000	7,000	6,000	7,000	7,000
WUXGA	XGA	WXGA	WUXGA with 4K Enhancement <sup>††</sup>	WXGA	WXGA	WUXGA with 4K Enhancement <sup>††</sup>	WUXGA with 4K Enhancement <sup>††</sup>	WUXGA with 4K Enhancement <sup>††</sup>
15.2 lb	28.4 lb	28.4 lb	28.4 lb	37.3 lb	37.3 lb	37.3 lb	37.3 lb	37.3 lb
18.5 x 13.9 x 6.2	20.7 x 16.7 x 7.5	20.7 x 16.7 x 7.5	20.7 x 16.7 x 7.5	21.5 x 7.4 x 19.1	21.5 x 7.4 x 19.1	21.5 x 7.4 x 19.1	21.5 x 7.4 x 19.1	21.5 x 7.4 x 19.1
15,000:1	50,000:1	50,000:1	50,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1
1.26 Wide, 2.30 Tele 1.0 – 1.8x Optical	See Chart for Lens Options			See Chart for Lens Options				
Lamp	Lamp	Lamp	Lamp	Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor
5,000/10,000	3,000/4,000 2,000 in Portrait Mode	3,000/4,000 2,000 in Portrait Mode	3,000/4,000 2,000 in Portrait Mode	20,000 <sup>†††</sup>	20,000 <sup>†††</sup>	20,000 <sup>†††</sup>	20,000 <sup>†††</sup>	20,000 <sup>†††</sup>
462 W	601 W	601 W	601 W	361 W	439 W	361 W	439 W	439 W
10 W	10 W	10 W	10 W	–	–	–	–	–
–	–	–	–	–	–	–	–	–
YES	YES	YES	YES	Digital	Digital	Digital	Digital	Digital
YES	YES	YES	YES	YES	YES	YES	YES	YES
–	YES	YES	YES	YES	YES	YES	YES	YES
–	YES	YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES	YES	YES
–	–	–	–	–	–	–	–	–
Manual/Auto	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual
–	–	–	–	–	–	–	–	–
V ±50%, H ±10%	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)
Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron, Control4	Crestron, AMX, Extron	Crestron, AMX, Extron	Crestron, AMX, Extron	Crestron, AMX, Extron	Crestron, AMX, Extron
HDMI x 2 (Includes MHL x 1) VGA x 2, Composite Video	HDMI x 1 (HDCP 2.2) VGA x 1, 5-BNC x 1	HDMI x 1 (HDCP 2.2) VGA x 1, 5-BNC x 1	HDMI x 1 (HDCP 2.2) VGA x 1, 5-BNC x 1	HDMI x 1 (HDCP 2.2) VGA x 1, 5-BNC x 1	HDMI x 1 (HDCP 2.2) VGA x 1, 5-BNC x 1	HDMI x 1 (HDCP 2.2) VGA x 1, 5-BNC x 1	HDMI x 1 (HDCP 2.2) VGA x 1, 5-BNC x 1	HDMI x 1 (HDCP 2.2) VGA x 1, 5-BNC x 1
RCA (L & R) x 1 Mini Stereo x 2	Mini Stereo x 3	Mini Stereo x 3	Mini Stereo x 3	Mini Stereo x 3	Mini Stereo x 3	Mini Stereo x 3	Mini Stereo x 3	Mini Stereo x 3
Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1
Type-A, Type-B	Type-B x 1 (For Service, Clone), Type-A x 1 (For Wireless, FW Update, Clone)			Type-B x 1 (For Service, Clone), Type-A x 1 (For Wireless, FW Update, Clone)				
–	DVI-D x 1	DVI-D x 1	DVI-D x 1	DVI-D x 1	DVI-D x 1	DVI-D x 1	DVI-D x 1	DVI-D x 1
HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)
–	–	–	–	–	–	–	–	–
Mini D-sub 15-pin x 1 RS-232c x 1	Mini D-sub 15-pin x 1 RS-232c x 1	Mini D-sub 15-pin x 1 RS-232c x 1	Mini D-sub 15-pin x 1 RS-232c x 1	Mini D-sub 15-pin x 1 RS-232c x 1	Mini D-sub 15-pin x 1 RS-232c x 1	Mini D-sub 15-pin x 1 RS-232c x 1	Mini D-sub 15-pin x 1 RS-232c x 1	Mini D-sub 15-pin x 1 RS-232c x 1
Universal Projector Mount (ELPMBPJG/ELPM3PRH)	HDBaseT Transmitter (ELPHD01)	HDBaseT Transmitter (ELPHD01)	HDBaseT Transmitter (ELPHD01)	HDBaseT Transmitter (ELPHD01)	HDBaseT Transmitter (ELPHD01)	HDBaseT Transmitter (ELPHD01)	HDBaseT Transmitter (ELPHD01)	HDBaseT Transmitter (ELPHD01)
V12H808001/V12H809001	V12H547020	V12H547020	V12H547020	V12H547020	V12H547020	V12H547020	V12H547020	V12H547020
HDBaseT Transmitter	Epson Mount for Low Ceiling/High Ceiling	Epson Mount for Low Ceiling/High Ceiling	Epson Mount for Low Ceiling/High Ceiling	Epson Mount for Low Ceiling/High Ceiling	Epson Mount for Low Ceiling/High Ceiling	Epson Mount for Low Ceiling/High Ceiling	Epson Mount for Low Ceiling/High Ceiling	Epson Mount for Low Ceiling/High Ceiling
V12H547020	Low - V12H802010 / High - V12H803010			Low - V12H802010 / High - V12H803010				

† 20,000 hours is the estimated laser light source life when used in Normal Mode. Actual hours may vary depending on mode and usage environment. The projector has a standard limited warranty of 3 years.  
†† 4K Enhancement Technology shifts each pixel to surpass Full HD resolution on screen.



**Large Venue Installation – Pro L Series**  
Laser Projectors with Optional Lenses

								
<b>Pro L1490UNL</b>	<b>Pro L1495UNL</b>	<b>Pro L1500UHL</b>	<b>Pro L1505UHL</b>	<b>Pro L1715SNL</b>	<b>Pro L1750UNL</b>	<b>Pro L1755UNL</b>	<b>Pro L12000QNL</b>	<b>Pro L12002QNL</b>
V11HA16920	V11HA16820	V11H910920	V11H910820	V11H890820	V11H892920	V11H892820	V11H832820	V11H832920
Laser	Laser	Laser	Laser	Laser	Laser	Laser	Laser	Laser
Pro L1300U	Pro L1405U	Pro L1500U	Pro L1505U	–	–	–	–	–
3-year or 20,000 hours	3-year or 20,000 hours	3-year or 20,000 hours	3-year or 20,000 hours	3-year or 20,000 hours	3-year or 20,000 hours	3-year or 20,000 hours	3-year or 20,000 hours	3-year or 20,000 hours
9,000	9,000	12,000	12,000	15,000	15,000	15,000	12,000	12,000
9,000	9,000	12,000	12,000	15,000	15,000	15,000	12,000	12,000
WUXGA with 4K Enhancement <sup>††</sup>	WUXGA with 4K Enhancement <sup>††</sup>	WUXGA with 4K Enhancement <sup>††</sup>	WUXGA with 4K Enhancement <sup>††</sup>	SXGA+	WUXGA with 4K Enhancement <sup>††</sup>	WUXGA with 4K Enhancement <sup>††</sup>	4K UHD	4K UHD
52.3 lb	52.3 lb	52.3 lb	52.3 lb	53.0 lb	53.2 lb	53.2 lb	113.3 lb	113.3 lb
23.1 x 19.4 x 8.3	23.1 x 19.4 x 8.3	23.1 x 19.4 x 8.3	23.1 x 19.4 x 8.3	23.1 x 19.4 x 8.3	23.1 x 19.4 x 8.3	23.1 x 19.4 x 8.3	24.4 x 14.1 x 31.1	24.4 x 14.1 x 31.1
2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1
See Chart for Lens Options								
Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor
20,000 <sup>††</sup>	20,000 <sup>††</sup>	20,000 <sup>††</sup>	20,000 <sup>††</sup>	20,000 <sup>††</sup>	20,000 <sup>††</sup>	20,000 <sup>††</sup>	20,000 <sup>††</sup>	20,000 <sup>††</sup>
645 W	645 W	955 W	955 W	1,082 W	1,082 W	1,082 W	1,741 W	1,741 W
–	–	–	–	–	–	–	–	–
–	–	–	–	–	–	–	–	–
Digital	Digital	Digital	Digital	Digital	Digital	Digital	Mechanical Shutter	Mechanical Shutter
YES	YES	YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES	YES	YES
–	–	–	–	–	–	–	–	–
–	–	–	–	–	–	–	–	–
–	–	–	–	–	–	–	–	–
–	–	–	–	–	–	–	–	–
YES	YES	YES	YES	YES	YES	YES	YES	YES
–	–	–	–	–	–	–	–	–
Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual
–	–	–	–	–	–	–	–	–
Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Built-in	Built-in
Crestron, AMX, Extron, Control4, Art-Net	Crestron, AMX, Extron, Control4, Art-Net	Crestron, AMX, Extron, Control4, Art-Net	Crestron, AMX, Extron, Control4, Art-Net	Crestron, AMX, Extron, Control4, Art-Net	Crestron, AMX, Extron, Control4, Art-Net	Crestron, AMX, Extron, Control4, Art-Net	Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net
HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)
VGA x 1, 5-BNC x 1	VGA x 1, 5-BNC x 1	VGA x 1, 5-BNC x 1	VGA x 1, 5-BNC x 1	VGA x 1, 5-BNC x 1	VGA x 1, 5-BNC x 1	VGA x 1, 5-BNC x 1	VGA x 1	VGA x 1
Mini Stereo x 3	Mini Stereo x 3	Mini Stereo x 3	Mini Stereo x 3	Mini Stereo x 3	Mini Stereo x 3	Mini Stereo x 3	–	–
Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	–	–
Type-B x 1 (For Service, Clone), Type-A x 1 (For Wireless, FW Update, Clone)							Type-A, Type-B	Type-A, Type-B
DVI-D x 1	DVI-D x 1	DVI-D x 1	DVI-D x 1	DVI-D x 1	DVI-D x 1	DVI-D x 1	DVI-D x 1	DVI-D x 1
HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)
3G-SDI	3G-SDI	3G-SDI	3G-SDI	–	3G-SDI	3G-SDI	12G-SDI	12G-SDI
Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1
RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1
HDBaseT Transmitter (ELPHD01)	HDBaseT Transmitter (ELPHD01)	HDBaseT Transmitter (ELPHD01)	HDBaseT Transmitter (ELPHD01)	HDBaseT Transmitter (ELPHD01)	HDBaseT Transmitter (ELPHD01)	HDBaseT Transmitter (ELPHD01)	Display Port x 2 (ELPIF03)	Display Port x 2 (ELPIF03)
V12H547020	V12H547020	V12H547020	V12H547020	V12H547020	V12H547020	V12H547020	V12H916F01	V12H916F01
Epson Mount for Low Ceiling/High Ceiling	Epson Mount for Low Ceiling/High Ceiling	Epson Mount for Low Ceiling/High Ceiling	Epson Mount for Low Ceiling/High Ceiling	Epson Mount for Low Ceiling/High Ceiling	Epson Mount for Low Ceiling/High Ceiling	Epson Mount for Low Ceiling/High Ceiling	Epson Mount for Low Ceiling/High Ceiling	Epson Mount for Low Ceiling/High Ceiling

Low - V12H802010 / High - V12H803010

<sup>††</sup> 20,000 hours is the estimated life when the projector is used in Normal Mode in an ordinary environment. Actual hours may vary depending on mode and usage environment. The projector has a limited warranty of 3 years or 20,000 hours, whichever comes first.

				Interactive Projectors – BrightLink Series					
									
<b>Pro L2000UUNL</b>	<b>Pro L20002UUNL</b>	<b>Pro L3000UUNL</b>	<b>Pro L30002UUNL</b>	<b>BrightLink® 536Wi</b>	<b>BrightLink 695Wi</b>	<b>BrightLink 725Wi</b>	<b>BrightLink 735Fi</b>	<b>BrightLink 1480Fi</b>	<b>BrightLink 1485Fi</b>
V11H833820	V11H833920	V11H944820	V11H944920	V11H670022	V11H740522	V11H998520	V11H997520	V11H921520	V11H919520
Laser	Laser	Laser	Laser	V13H010L87	V13H010L91	Laser	Laser	Laser	Laser
–	–	–	–	BrightLink 436Wi	BrightLink 595Wi	–	–	BrightLink Pro	BrightLink Pro
3-year or 20,000 hours	3-year or 20,000 hours	3-year or 20,000 hours	3-year or 20,000 hours	2-year	2-year	3-year	3-year	3-year	3-year
20,000	20,000	30,000	30,000	3,400	3,500	4,000	3,600	5,000	5,000
20,000	20,000	30,000	30,000	3,400	3,500	4,000	3,600	5,000	5,000
WUXGA	WUXGA	WUXGA with 4K Enhancement**	WUXGA with 4K Enhancement**	WXGA	WXGA	WXGA	1080p	Full HD 1080p	Full HD 1080p
109.3 lb	109.3 lb	140.7 lb	141.5 lb	8.5 lb	12.8 lb	12.7 lb	12.7 lb	21.4 lbs	21.4 lbs
24.4 x 14.1 x 31.1	24.4 x 14.1 x 31.1	31.1 x 28 x 11.4	31.1 x 28 x 11.4	31.1 x 28 x 11.4	14.5 x 15.8 x 5.9	14.1 x 15.6 x 5.25	14.1 x 15.6 x 5.25	18.1 x 14.3 x 8.3	18.1 x 14.3 x 8.3
2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1	16,000:1	14,000:1	2,500,000:1	2,500,000:1	2,500,000:1	2,500,000:1
See Chart for Lens Options		Optional Lenses		0.48 Wide, 0.65 Tele 1.35x Digital	0.28 Wide, 0.37 Tele 1.35x Digital	0.28 Wide, 0.37 Tele 1.35x Digital	0.26 Wide, 0.36 Tele 1.35x Digital	0.27 Wide, 0.37 Tele 1.35x Digital	0.27 Wide, 0.37 Tele 1.35x Digital
Laser Phosphor	Laser Phosphor	Laser Phosphor	Laser Phosphor	Lamp	Lamp	Laser	Laser	Laser	Laser
20,000**	20,000**	20,000**	20,000**	5,000/10,000	5,000/10,000	20,000/30,000	20,000/30,000	20,000**	20,000**
1,860 W	1,860 W	2,325 W	2,325 W	315 W	373 W	267 W	267 W	381 W	381 W
–	–	–	–	16 W	16 W	16 W	16 W	2x 8 W	2x 8 W
–	–	–	–	YES	YES	YES	YES	YES	YES
Mechanical Shutter	Mechanical Shutter	Mechanical Shutter	Mechanical Shutter	Digital	Digital	Digital	Digital	Digital	Digital
YES	YES	YES	YES	–	–	YES	YES	YES	YES
YES	YES	YES	YES	–	–	–	–	–	YES
YES	YES	YES	YES	–	–	–	–	–	–
YES	YES	YES	YES	–	–	YES	YES	YES	YES
YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
–	–	–	–	–	–	–	–	–	–
Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Auto	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual
–	–	–	–	–	–	–	–	–	–
Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	Powered with Lens Memory	–	–	–	–	–	–
RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)	RJ-45 (Content over IP)
Built-in	Built-in	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Optional (802.11 b/g/n)	Included 802.11 a/b/g/n/ac; 5GHz	Included 802.11 a/b/g/n/ac; 5GHz	Included 802.11 a/b/g/n/ac; 5GHz	Included 802.11 a/b/g/n/ac; 5GHz
Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron, Art-Net	Crestron, AMX, Extron	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink	Crestron, AMX, Extron, Control4, PJLink
HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1 (HDCP 2.2)	HDMI x 1	VGA x 2, Composite Video	HDMI x 3	HDMI x 3	HDMI x 3	HDMI x 3
VGA x 1, 5-BNC x 1	VGA x 1, 5-BNC x 1	VGA x 1, 5-BNC x 1	VGA x 1, 5-BNC x 1	VGA x 2, S-video, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video	VGA x 2, Composite Video
–	–	–	–	RCA (L & R) x 1 Mini Stereo x 2 Mic-in	Mini Stereo x 3 Mic-in	Mini Stereo x 3 Mic-in	Mini Stereo x 3 Mic-in	Mini Stereo x 3 Mic-in	Mini Stereo x 3 Mic-in
–	–	–	–	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1	Mini Stereo x 1
Type-A, Type-B	Type-A, Type-B	Type-A, Type-B	Type-A, Type-B	Type-A, Type-B	Type-A, Type-B	Type-B x 2, Type-A x 1	Type-B x 2, Type-A x 1	Type-B x 2, Type-A x 2 (Memory Stick & Doc Camera)	Type-B x 2, Type-A x 2 (Memory Stick & Doc Camera)
DVI-D x 1	DVI-D x 1	DVI-D x 1	DVI-D x 1	–	–	–	–	–	–
HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	HDBaseT x 1 (HDCP 2.2)	–	–	–	–	–	HDBaseT x 1 (HDCP 2.2)
3G-SDI	3G-SDI	3G-SDI	3G-SDI	–	–	–	–	HDMI - Out	HDMI - Out
Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1	Mini D-sub 15-pin x 1
RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1	RS-232c x 1
Display Port x 2 (ELPIF03)	Display Port x 2 (ELPIF03)	HDBaseT Transmitter (ELPHD01)	HDBaseT Transmitter (ELPHD01)	Short-throw Wall Mount (ELPMB27)	–	Ultra Short-throw Wall Mount (ELPMB62)	Ultra Short-throw Wall Mount (ELPMB62)	Ultra Short-throw Wall Mount (ELPMB62)	
V12H916F01	V12H916F01	V12H547020	V12H547020	V12H706020	V12H777020	V12HA06A05	V12HA06A05	V12HA06A05	V12HA06A05
Epson Mount for Low Ceiling/High Ceiling	Epson Mount for Low Ceiling/High Ceiling	–	–	Wireless LAN Module	–	100" Whiteboard 16:9 or Da-Lite® IDEA® Screen Whiteboard 16:9	100" Whiteboard 16:9 or Da-Lite IDEA Screen Whiteboard 16:9	100" Whiteboard 16:9 or Da-Lite IDEA Screen Whiteboard 16:9	100" Whiteboard 16:9 or Da-Lite IDEA Screen Whiteboard 16:9
–	–	–	–	V12H418P12	–	V12HA06A02 or V12HA06A01			

Note: Highlighted boxes indicate step-ups between models within a series.	Interactive Projectors – BrightLink Series						
	Interactive Specs						
	BrightLink 536Wi	BrightLink 685Wi	BrightLink 695Wi	BrightLink 725Wi	BrightLink 735Fi	BrightLink 1480Fi	BrightLink 1485Fi
<b>Interactive Features</b>							
Pens	1 Pen Included, Dual-user Support	2 Pens Included, Dual-user Support	2 Pens Included, Dual-user Support	2 Pens Included, Dual-user Support	2 Pens Included, Dual-user Support	2 Pens Included, Dual-user Support	2 Pens Included, Dual-user Support
Pen Technology	IR, 850nm						
Finger Touch	–		YES, up to 6 fingers	Optional, up to 6 fingers	Optional, up to 6 fingers	Optional, up to 6 fingers	YES, up to 6 fingers
Interactive Pen Functions	Mouse Function (Left/Right Click), Digital Pen, LED Battery Status Indicator						
PC-free Whiteboard Sharing	–	–	–	YES	YES	YES	YES
DuoLink Extended Whiteboard <sup>o</sup>	–	YES	YES	NO	NO	NO	YES, with Edge Blending
Calibration	Automatic or Manual						
Interactive Image Size	53" – 116"	60" – 100"	60" – 100"	16:10 up to 100"	16:9 up to 100" 16:6 up to 110"	16:9 up to 100"	16:9 up to 100" 16:6 up to 120"
Interactive Connectivity	USB or LAN	USB or LAN	USB or LAN	USB, Miracast, LAN	USB, Miracast, LAN	USB, Miracast, LAN	USB, Miracast, LAN
PC-free Annotation	YES	YES	YES	YES	YES	YES	YES
PC-free Digital Whiteboard	1 page	1 page	1 page	Up to 20 pages	Up to 20 pages	Up to 20 pages	Up to 20 pages
Wall-mounted Control Panel	–	–	–	–	–	–	YES
PC-free Save, Email, Print	–	Save, Print	Save, Print	Yes	Yes	YES	YES
Gestures Support	YES, computers require Windows® 7/8/10 or Mac® OS 10.x						
Included Software	Easy Interactive Tools for PC/Mac, Built-in Annotation Toolbar, SMART Learning Suite						




<sup>o</sup>Requires Easy Interactive Driver. Certain functionality is only available through Epson Interactive Tools (EIT) software. For a list of supported operating systems, visit [www.epson.com](http://www.epson.com)

Lenses Compatible with Pro G7000 Series Projectors and the Pro L1060U, Pro L1070U, Pro L1075U, Pro L1060W and Pro L1070W										
Model	Ultra Short-throw Lens	Short Lens #1	Short Lens #2	Wide Lens #1	Wide Lens #2	Middle Lens #1	Middle Lens #2	Middle Lens #3	Middle Lens #4	Long Lens
Product Code	V12H004X01	V12H004UA3	V12H004U04	V12H004W05	V12H004W06	V12H004M08	V12H004M0F	V12H004M0A	V12H004M0B	V12H004L08
White Version	V12H004Y01	–	–	–	–	–	–	–	–	–
Zoom Ratio	1.0	1.0 – 1.2x	1.0 – 1.2x	1.0 – 1.4x	1.0 – 1.4x	1.0 – 1.6x	1.0 – 1.6x	1.0 – 1.5x	1.0 – 1.5x	1.0 – 1.4x
Throw Ratio (16:10)	0.35	0.65 – 0.78	0.87 – 1.05	1.04 – 1.46	1.62 – 2.22	1.44 – 2.32	2.16 – 3.48	3.32 – 5.06	4.85 – 7.38	7.21 – 10.11

Lenses Compatible with Pro L Projectors from 9,000 to 20,000 lumens										
Model	Ultra Short-throw Lens	Short Lens #1	Short Lens #2	Wide Lens #1	Wide Lens #2	Wide Lens #3	Middle Lens #2	Middle Lens #3	Middle Lens #4	Long Lens
Product Code	V12H004X02	V12H004UA3	V12H004U04	V12H004W05	V12H004W06	V12H004W08	V12H004M0F	V12H004M0A	V12H004M0B	V12H004L08
White Version	V12H004Y02	–	–	–	–	–	–	–	–	–
Zoom Ratio	1.0	1.0 – 1.2x	1.0 – 1.2x	1.0 – 1.4x	1.0 – 1.4x	1.0 – 1.4x	1.0 – 1.6x	1.0 – 1.5x	1.0 – 1.5x	1.0 – 1.4x
Throw Ratio (16:10)	0.35	0.48 – 0.57	0.64 – 0.77	0.77 – 1.07	1.19 – 1.62	0.86 – 1.21	1.57 – 2.56	2.42 – 3.71	3.54 – 5.41	5.27 – 7.41

## An essential teaching tool for the modern classroom

Share books, 3D objects, and detailed demonstrations or experiments with your entire class using Epson's easy-to-use document cameras. Record lessons for viewing at a later time, and give your students a more interactive learning experience.

Document Cameras			
			
Model	DC-07	DC-13	DC-21
Product Code	V12H759020	V12H757020	V12H758020
Zoom	8x digital	16x digital	12x optical, 10x digital
Pixel Count	2MP	2MP	2MP
Output Resolution (Max.)	1080p	1080p	1080p
Frame Rate	15 fps	30 fps	30 fps
Connectivity (Output)	USB	USB, VGA, HDMI	USB, VGA, HDMI
Capture Area	10.7" x 14.3"	11.7" x 20.7"	11.7" x 20.7"
A/V Recording	YES	YES	YES
Built-in Microphone	YES	YES	YES
Microscope Adapter	–	YES	YES
SD Card Slot <sup>o</sup>	–	YES	YES
Software Included	YES	YES	YES

<sup>o</sup>SD card sold separately.

## Comprehensive Warranty with Convenient Road Service

Epson projector customers receive first-class service with Epson's standard 2-year limited warranty, including Road Service and a dedicated toll-free support line. Epson laser projectors receive a standard 3-year limited warranty.<sup>o</sup>

<sup>o</sup>Lamps have a 90-day limited warranty. Pro G and Pro L Series projectors are warranted for 3 years or 20,000 hours, whichever comes first. Select Pro L projectors do not offer "Road Service."

**Note:** Highlighted boxes indicate step-ups between models within a series.

Epson Model

Product Code

Replacement Lamp Code

Previous Epson Model

Road Service Limited Warranty

### Basics

Color Brightness (Color Lumens)\*

White Brightness (White Lumens)\*

Native Resolution\*\*

Weight

Dimensions (Inches)†

Contrast Ratio (up to)

Throw Ratio

Zoom Lens (Ratio)

Light Source

Light Source Life Cycle up to (Normal/Medium/ECO [Hours])††

Power Consumption

### Value-added Features

Built-in Speaker

Closed Captioning

A/V Mute

Split Screen

Edge Blending

Curved Wall, Corner Wall

Scheduling Function

### Easy Connectivity and Setup

Epson iProjection Suite (Moderator, Multi-PC, Device Management)\*\*\*

Epson Creative Content Projection App for Signage\*\*\*\*

Epson Projector Content Manager Software\*\*\*\*

Miracast

USB Plug 'n Play Image/Video

PC-free Presentations via USB Type-A

Quick Corner Adjustments

Screen Fit

Keystone (Horizontal/Vertical)

Easy-slide Horizontal Keystone Adjustment

Lens Shift (Vertical and Horizontal)

### LAN Networking and Control

Wired

Wireless

Compatible Control Systems

### Connections

HDMI

Analog Connections

Audio In

Variable Audio Out

USB 2.0 Connectors

DisplayPort/DVI-D

HDBaseT

SDI

Monitor Out

Serial Control

### Recommended Accessory 1

### Recommended Accessory 1 SKU

### Recommended Accessory 2

### Recommended Accessory 2 SKU



## LightScene® Accent Lighting Laser Projectors

A convergence of lighting and display technology, LightScene laser projectors captivate audiences by simultaneously illuminating and projecting on virtually any surface or material. This groundbreaking solution elevates ordinary spaces into stunning visual environments, unleashing dynamic, experiential content for digital art, spatial design, signage and wayfinding applications.

LightScene Projectors				
Epson Model	EV-100	EV-105	EV-110	EV-115
Product Code	V11H868020	V11H868120	V11HA22020	V11HA22120
Product Color	White	Black	White	Black
Road Service Limited Warranty	3 years or 20,000 hours, whichever comes first			
Color Brightness (Color Lumens)*	2,000	2,000	2,200	2,200
White Brightness (White Lumens)*	2,000	2,000	2,200	2,200
Native Resolution	WXGA (1280 x 800)			
Edge Blending Capable	YES			
Contrast Ratio (Dynamic)	Up to 2,500,000:1			
Light Source Life Up To	20,000 hours**			
Left/Right Up/Down Movement	180 degrees			
Ball-joint Axis Rotation	360 degrees			
Zoom (Powered)	1.58x			
HDMI SD Card Slot	1x HDMI 1x SD Card Slot			
Variable Audio Out	1x Stereo Mini Out			
GPI Motion Sensor Compatible	–	–	YES	YES
Bluetooth Audio	–	–	YES	YES
Epson Projector Content Manager Software***	YES			
Epson Creative Content Projection App for Signage***	YES			

\*Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118.

\*\*No required maintenance for the light source for up to 20,000 hours. Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m<sup>3</sup> of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period.

\*\*\*Internet connection required for download. Data usage fees may apply.

# Epson Laser Projection Technology

As a world leader in digital 3LCD projection solutions, Epson continues to drive the future of projection technology with its full suite of laser projectors and displays. Featuring lamp-free, long-life, laser light engines, Epson laser solutions achieve new levels of performance and reliability<sup>1</sup>.

## Why Choose Laser?

**Breakthrough laser technology** — long-life laser light engine provides up to 20,000 hours of light source life<sup>1</sup>






**Outstanding color performance and contrast** — get exceptional, true-to-life color reproduction and deep, dark blacks for stunning visuals you can count on for an array of applications

**Instant Off<sup>®</sup>/On** — displays and projectors reach maximum brightness and turn off almost immediately, without having to warm up or cool down

**Reliable operation** — ideal for applications requiring extended projection



### Explore Epson's Suite of Laser Projectors and Displays

				
<b>Laser Large-venue Projectors</b>	<b>Laser Interactive Displays</b>	<b>Portable Laser Display Projectors</b>	<b>Ultra Short-throw Display Projectors</b>	<b>Lighting Laser Display Projectors</b>
High-lumen laser projectors designed for exceptional performance in large venues	Full HD, ultra short-throw interactive laser displays for collaborative meetings and learning	High-performance laser projectors offering a variety of brightness, connectivity and resolution	Bold, rich, Full HD laser displays for virtually any application, including those in small spaces, without any shadows	Project dynamic, experiential content for digital art, commercial signage and décor applications

## Epson Business Solutions

Epson is a leading provider of innovative technology solutions that help businesses succeed. We partner with you to best meet your specific needs, focusing on:

- Improved productivity
- World-class customer service and support
- Cost-effective, high-quality solutions
- A commitment to the environment

Discover how Epson can help you work toward the future [www.epson.com/forbusiness](http://www.epson.com/forbusiness)

**Epson America, Inc.**  
3131 Katella Avenue, Los Alamitos, CA 90720

[www.epson.com](http://www.epson.com)  
[www.epson.com/projectors](http://www.epson.com/projectors)

<sup>1</sup> Large-venue series: 20,000 hours is the estimated life when the projector is used in Normal Mode in an ordinary environment. Actual hours may vary depending on mode and usage environment. The projector has a limited warranty of 3 years or 20,000 hours, whichever comes first; Interactive, Digital Signage and Accent Lighting projectors: 20,000 hours is the estimated projector life when used in Normal Mode. Actual hours may vary depending on mode and usage environment. Interactive and Digital Signage projectors come with a 3-year limited warranty; Accent Lighting projectors have a limited warranty of 3 years or 20,000 hours, whichever comes first; Corporate series: 20,000 hours is the estimated laser light source life when used in Normal Mode. Actual hours may vary depending on mode and usage environment. The projector has a standard limited warranty of 3 years.

Specifications and terms are subject to change without notice. EPSON, Instant Off, PowerLite, LightScene and Quick Corner are registered trademarks, EPSON Exceed Your Vision is a registered logomark and Epson iProjection is a trademark of Seiko Epson Corporation. BrightLink is a registered trademark and Pilot is a trademark of Epson America, Inc. Mac is a trademark of Apple Inc., registered in the U.S. and other countries. Windows is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. Miracast<sup>®</sup> is a registered trademark of Wi-Fi Alliance<sup>®</sup>. Da-Lite and IDEA Screen are registered trademarks of Milestone AV Technologies. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2020 Epson America, Inc. CPD-52535R8 12/20