

# LG Cloud Device All-in-One Thin Client

## 27-inch All-in-One Thin Client with Pop-up Webcam and IGEL

27CN650i-6N

27-inch Full HD (1920x1080) IPS Display

**Quad-core Processor** (Intel® Celeron J4105)

**Adjustable Stand** 

(Tilt, Height, Bi-Directional Pivot)

**Multi Display Setup** 

(Up to 2 Displays with up to 4K Resolution)

Fanless Design

Full HD Webcam (Pop-up Type)

**Built-in Speakers** 

Ships with IGEL operating system (free trial)





#### **Efficient Work Environment**

Work comfortably with an IPS display with clear images at any angle. Increase your productivity with a more spacious workspace. Enjoy a clean setup with fewer cables and wires, and convenient stand that adjusts to your height, and a monitor that tilts for your comfort. Feel free to adjust, swivel, and pivot to help you be more productive at work.

#### **Improved Performance**

Work faster than ever with an advanced Quad-core Processor (Intel® Celeron J4105) and powerful memory capacity. Stay productive with a multi-monitor set-up supporting up to 2 displays with 4K UHD resolution. This all-in-one has a simplified, fanless design with fewer parts for maintenance.

#### **Seamless Connectivity**

Host online meetings and video conferences with a built-in Full HD pop-up webcam and integrated speakers. The 27CN650i-6N conveniently has multiple connections for one USB Type-C™, two USB 2.0, and four USB 3.1 ports. Maximize productivity with Wi-Fi and Bluetooth wireless connections to work on VDIs in any environment.

## All-in-One Thin Client with Pop-up Webcam and IGEL

27CN650i-6N

## **Specifications**

	Model Name	27CN650i-6N
Display	Diagonal	27"
	Aspect Ratio	16:9
	Panel Type	IPS
	Resolution	Full HD (1920 x 1080)
	Brightness	300 nits (Typ.)
	Contrast Ratio	1,000:1 (Typ.)
	Response Time (GTG) <sup>1</sup>	5ms
	Viewing Angle (CR≥10)	178° x 178°
System	Processor	Intel® Celeron J4105 (Quad Core 1.5GHz, up to 2.5GHz burst)
	OS	IGEL operating system preloaded (free trial)
	Memory	4GB DDR4
	Graphics	Integrated
	Storage (SSD)	16GB eMMC
Connectivity	DisplayPort	1 x DisplayPort (Output)
	HDMI	1 x HDMI (Input)
	USB	2x USB 2.0, 4 x USB 3.1 gen1, 1 x USB Type-C™
	Mic-in	Mic-in & Headphone Out Combo
	Headphone Out	
	Wireless	Dual Band 802.11a/b/g/n/ac 2x2 (BT 5.0 Combo, Internal Antenna)
Network	LAN	1 x RJ45 : 10/100/1000 Base-T Gigabit Ethernet (Wake on LAN)
	ВТ	BT5.0
Sound	Built-in Stereo Speakers	3W x 2
	Dimensions with Stand (W x H x D)	24.5 x 9.4 x 20.9 (in) / 622.3 x 239.6 x 531.7 (mm)
	Shipping Dimensions (W x H x D)	27.8 × 20.3 × 9.2 (in) / 707 × 516 × 233 (mm)
Mechanical	Dimensions without Stand (W x H x D)	24.5 × 2.4 × 14.6 (in) / 622.3 × 61.0 × 371.5 (mm)
	Weight with Stand	17.19 lbs / 7.8kg
	Weight without Stand	12.34 lbs / 5.6kg
	Shipping Weight	23.1 lbs / 10.5 kg
	VESA	3.9 x 3.9 (in) /100 x 100 (mm)
	Adjustable Stand	Pivot : Bi-Direction, Swivel : 0°-355° ( $\pm$ 5°), Tilt : -5°-35°, Height Range : 130mm
	UPC	1 95174 03156 8
Webcam	Webcam	Yes (Pop-up Type)
Security	ТРМ	Hardware TPM 2.0

<sup>1)</sup> GTG: Gray to gray response time





